


# Map tiles

Patrick Brown



April 9, 2014

The following are some examples of maps produced with  
`mymap=openmap(x, path="something")`

```
1 plot (openmap(x,path=" osm "))
```



```
2 plot (openmap(x,path=" osm-no-labels "))
```




```
3 plot (openmap(x,path=" osm-transport "))
```



```
4 plot (openmap(x,path=" bw-mapnik "))
```



```
5 plot RGB (openmap(x,path=" mapquest "))
```



6 `plot RGB (openmap(x,path=" mapquest-sat "))`



7 `plot (openmap(x,path=" landscape "))`



8 `plot (openmap(x,path=" opentopomap "))`


opentopomap (x,  
rank as, zoom up  
available)



```
9 plot (openmap(x,path=" maptoolkit "))
```



```
10 plot (openmap(x,path=" waze "))
```



```
11 plot (openmap(x,path=" mapbox "))
```

mapbox is  
not currently  
available

```
12 plot (openmap(x,path=" humanitarian "))
```



```
13 plot (openmap(x,path=" parking-bw "))
```



```
14 plot (openmap(x,path=" osm-locale-de "))
```



```
15 plot (openmap(x,path=" bw-noicons "))
```



```
16 plot (openmap(x,path=" osm-labels-en "))
```



```
17 plot (openmap(x,path=" osm-labels-fr "))
```



```
18 plot (openmap(x,path=" osm-labels-de "))
```



```
19 plot (openmap(x,path=" osm-labels-it "))
```




```
20 plot (openmap(x,path=" osm-labels-es "))
```



```
21 plot (openmap(x,path=" osm-labels-ru "))
```



```
22 plot (openmap(x,path=" stamen-toner "))
```



```
23 plot RGB (openmap(x,path=" stamen-watercolor "))
```

