



R Package **gdistance**: Distances and Routes on Geographical Grids

Jacob van Etten

Abstract

The R package **gdistance** provides classes and functions to calculate various distance measures and routes in heterogeneous geographic spaces represented as grids. Least-cost distances as well as more complex distances based on (constrained) random walks can be calculated. Also the corresponding routes or probabilities of passing each cell can be calculated. The package implements classes to store the data about the probability or cost of transitioning from one cell to another on a grid in a memory-efficient sparse format. These classes make it possible to manipulate the values of cell-to-cell movement directly, which offers flexibility and the possibility to use asymmetric values. The novel distances implemented in the package are used in geographical genetics (applying circuit theory), but may also have applications in other fields of geospatial analysis.

Keywords: geospatial analysis, landscape genetics, circuit theory, connectivity, dispersal, travel, least-cost path, least-cost distance, random walk, R.

1. Introduction: the crow, the wolf, and the drunkard

This article describes **gdistance**, a package written for use in the R environment (R Development Core Team 2014). It provides functionality to calculate various distance measures and routes in heterogeneous geographic spaces represented as grids. Distance is fundamental to geospatial analysis (Tobler 1970). It is closely related to the concept of route. For example, take great-circle distance, the most commonly used geographic distance measure. This distance represents the shortest line between two points, taking into account the curvature of the earth. Implicit in this distance measure is a route. The great-distance distance could be conceived of as the distance measured along a route of a very efficient traveller who knows where to go and has no obstacles to deal with. In common language, this is referred to as a distance ‘as the crow flies’.

Other distance measures also imply a route across geographic space. The least-cost distance

is implemented in most GIS software and mimics route finding ‘as the wolf runs’¹, taking into account obstacles and the local ‘friction’ of the landscape. Since least-cost distance is affected by the environment, grid-based calculations are necessary. Other grid-based distances have been developed based on the random walk or drunkard’s walk, in which route-finding is a stochastic process.

Package **gdistance** was designed to determine such grid-based distances and routes and to make it possible to use these measures in combination with other functionality available within R. It has functionality that is comparable to other software such as ArcGIS Spatial Analyst (McCoy and Johnston 2002), GRASS GIS (GRASS Development Team 2012), and CircuitScape (McRae *et al.* 2008). The **gdistance** package also contains specific functionality for geographical genetic analyses, not found in other software yet. The package implements measures to model dispersal histories first presented by van Etten and Hijmans (2010) (see Section 7 and Example 2 below).

2. Theory

In **gdistance** calculations are done in various steps. At first, this tends to be somewhat confusing for those who are used to distance and route calculations in GIS software, which are usually done in a single step. However, an important goal of **gdistance** is to make the calculations of distances and routes more flexible, which also makes the package somewhat more complicated to use. Users, therefore, need to have a basic understanding of the theory behind distance and route calculations.

Calculations of distances and routes start with raster data. In geospatial analysis, rasters are rectangular, regular grids that represent continuous data over geographical space. Cells arranged in rows and columns and each holds a value. A raster is accompanied by metadata that indicate the resolution, extent and other properties.

Distance and route calculations on rasters rely on graph theory. So as a first step, rasters are converted into graphs by connecting cell centres to each other, which become the nodes in the graph. This can be done in various ways (Figure 1).

- Cells can be connected orthogonally to their four immediate neighbours, the von Neumann neighbourhood.
- Cells can be connected with their eight orthogonal and diagonal nearest neighbours, the Moore neighbourhood. The resulting graph is called the king’s graph, because it reflects all the legal movements of the king in chess. This is the most common and often only way to connect grids in GIS software.
- Connecting in 16 directions combines king’s and knight’s moves. The function `r.cost` in the software GRASS (GRASS Development Team 2012) has this as an option, which inspired its implementation in **gdistance**. The section on distance transforms in de Smith *et al.* (2009) also discusses 16-cell neighbourhoods. Connecting in 16 directions may increase the accuracy of the calculations.

When the raster is converted into a graph, weights are given to each edge (connections between nodes). These weights correspond to different concepts. In most GIS software, distance

¹There are some variations on this expression, involving mostly other animals, or telecom cables.




Figure 1: Rasters can be converted into graphs in different ways.

analyses are done with calculations using cost, friction or resistance values. In graph theory, weights can also correspond to conductance ($1/\text{resistance}$), which is equivalent to permeability (a term used in landscape ecology). The weights can also represent probabilities of transition.

Graphs are mathematically represented as matrices to do calculations. These can include transition probability matrices, adjacency matrices, resistance/conductance matrices, Laplacian matrices, among others. In **gdistance**, we refer collectively to these matrices to represent graphs as ‘transition matrices’. These transition matrices are the central object in the package; all distance calculations need one or more transition matrices as an input.

In **gdistance**, conductance rather than resistance values are expected in the transition matrix. An important advantage of using conductance is that it makes it possible to store values in computer memory very efficiently, using so-called sparse matrices. Sparse matrices only store non-zero values and indices that locate these values in the rows and columns of the matrix. Zero values are not being stored in memory. Conductance matrices usually contain mainly zeros, because cells are connected only with adjacent cells, and the conductance for direct connections between remote cells is zero. This would not be the case if resistance matrices were used, as resistance is infinite (∞) between unconnected cells and these values would fill up the matrix.

The calculation of the edge weights or conductance values is usually based on the values of the pair of grid cells to be connected. These cell values represent a property of the landscape. For instance, from a grid with altitude values, a value for the ease of walking can be calculated for each transition between cells. In **gdistance**, users define a function $f(i, j)$ to calculate the transition value for each pair of adjacent cells i and j . With this approach, it is possible to create asymmetric matrices, in which the conductance from cell i to adjacent cell j is not always the same as the conductance from j back to i . This is relevant, among other things, for modelling travel in hilly terrain, as shown in Example 1 below. On the same slope, a downslope traveler experiences less friction than an upslope traveler. In this case, the function to calculate conductance values is non-commutative: $f(i, j) \neq f(j, i)$.

A problem that arises in grid-based modelling is the choice of weights that should be given to diagonal edges in proportion to orthogonal ones. For least-cost path distance and routes, this is fairly straightforward: weights are given in proportion to the distances between the cell centres. In a grid in which the orthogonal edges have a length of 1, the diagonal edges are $\sqrt{2}$ long. [McRae \(2006\)](#) applies this same idea to random walks. However, as [Birch \(2006\)](#) explains, for random walks this is generally not the best discrete approximation of the dispersal process in continuous space. Different orthogonal and diagonal weights could be considered based on his analytical results.

For random walks on longitude-latitude grids, there is an additional consideration to be made. Considering the eight neighbouring cells in a Moore's neighbourhood, the three cells that are located nearer to the equator are larger in area than the three cells that are closer to the nearest pole, as the meridians converge when moving from the equator to either pole. So the cells closer to the poles should have a slightly lower probability of being reached during a random walk from the central cell. More theoretical work is needed to investigate possible solutions to this problem. For projected grids and small areas, we can safely ignore this distortion problem.

When the transition matrix has been constructed, different algorithms to calculate distances and routes are applied.

- The least-cost distance mimics route finding 'as the wolf runs', taking into account obstacles and the local 'friction' of the landscape. The least-cost path between two cells on the grid and the associated distance can be obtained with Dijkstra's algorithm (Dijkstra 1959) or more sophisticated ones.
- A second type of route-finding is the random walk, which has no predetermined destination (a 'drunkard's walk'). Commute distance represents the random walk commute time, e.g., the average number of edges traversed during a random walk from an starting point on the graph to a destination point and back again to the starting point (Chandra *et al.* 1996). Resistance distance reflects the average travel cost during this walk (McRae 2006). When taken on the same graph these two measures differ only in their scaling (Kivimäki *et al.* 2012). Commute and resistance distances are calculated using the analogy with an electrical circuit (see Doyle and Snell 1984, for an introduction). The algorithm that **gdistance** uses to calculate commute distances was developed by Fouss *et al.* (2007).
- A third type of route-finding is by randomised shortest paths, which are an intermediate form between shortest paths and Brownian random walks, introduced by Saerens *et al.* (2009). By setting a parameter, θ (theta), in the randomised shortest paths calculation, distances and routes can be made more randomised. A lower value of θ means that walkers explore more around the shortest path. When θ approaches zero, the randomised shortest paths approach a random walk. van Etten and Hijmans (2010) applied randomised shortest paths in geospatial analysis (and see Example 2 below).

3. Raster basics

Analyses in **gdistance** start with one or more rasters. For this, it relies on another R package, **raster** (Hijmans and van Etten 2012). The **raster** package provides comprehensive geographical grid functionality. Here, we briefly discuss this package, referring the reader to the documentation of **raster** itself for more information.

The following code shows how to create a raster object.

```
R> library("gdistance")
R> r <- raster(ncol=3,nrow=3)
R> r[] <- 1:ncell(r)
R> r
```

```
class      : RasterLayer
dimensions : 3, 3, 9  (nrow, ncol, ncell)
resolution : 120, 60  (x, y)
extent     : -180, 180, -90, 90  (xmin, xmax, ymin, ymax)
coord. ref.: +proj=longlat +datum=WGS84
data source: in memory
names      : layer
values     : 1, 9  (min, max)
```

The first line loads the package **gdistance**, which automatically loads the package **raster** as well. The second line creates a simple raster with 3 columns and 3 rows. The third line assigns the values 1 to 9 as the values of the cells. The resulting object is inspected in the fourth line. As can be seen in the output, the object does not only hold the cell values, but also holds metadata about the geographical properties of the raster.

It can also be seen that this is an object of the class **RasterLayer**. This class is for objects that hold only one layer of grid data. There are other classes which allow more than one layer of data: **RasterStack** and **RasterBrick**. Collectively, these classes are referred to as **Raster***.

A class is a static entity designed to represent objects of a certain type using ‘slots’, which each hold different information about the object. Both **raster** and **gdistance** use so-called S4 classes, a formal object-oriented system in R. An advantage of using classes is that data and metadata stay together and remain coherent. Consistent use of classes makes it more difficult to have contradictions in the information about an object. For example, changing the number of rows of a grid also has an effect on the total number of cells. Information about these two types of information of the same object could become contradictory if we were allowed to change one without adjusting the other. Classes make operations more rigid to avoid such contradictions. Operations that are geographically incorrect can also be detected in this way. For example, when the user tries to add the values of two rasters of different projections, the **raster** package will detect the difference in the slots that hold the projection information of the two objects and throw an error.

Classes also make it easier for the users to work with complex data and functions. Since so much information can be stored in a consistent way in objects and passed to functions, these functions need fewer options. Functions can deduce from the class of the object that is given to it, what it needs to do. The use of classes, if well done, tends to produce cleaner, better readable, and more consistent scripts.

One important thing to know about **raster** is how grid data are stored internally in **Raster*** objects. Consecutive cell numbers in rasters go from left to right and from top to bottom. The 3 x 3 raster we just created with its cell numbers is shown in Figure 2.

Figure 2 was made with the following lines of code.

```
R> plot(r, main="r")
R> text(r)
```




Figure 2: Cell numbers of a 3 x 3 raster.

4. Transition* classes

As explained in Section 2 on the theory behind **gdistance**, transition matrices are the backbone of the package. The central classes in **gdistance** are **TransitionLayer** and **TransitionStack**. Most functions in the package have an object of one of these classes as input or output.

Transition* objects can be constructed from an object of class **Raster***. A **Transition*** object takes the necessary geographic references (projection, resolution, extent) from the original **Raster*** object. It also contains a matrix which represents a transition from one cell to another in the grid. Each row and column in the matrix represents a cell in the original **Raster*** object. Row 1 and column 1 in the transition matrix correspond to cell 1 in the original raster, row 2 and column 2 to cell 2, and so on. For example, the raster we just created would produce a 9 x 9 transition matrix with rows and columns numbered from 1 to 9 (see Figure 3 below).

The matrix is stored in a sparse format, as discussed in Section 2. The package **gdistance** makes use of sparse matrix classes and methods from the package **Matrix**, which gives access to fast procedures implemented in the C language (Bates and Maechler 2012).

The construction of a **Transition*** object from a **Raster*** object is straightforward. We can define an arbitrary function to calculate the conductance values from the values of each pair of cells to be connected.

In the following chunk of code, we use the **RasterLayer** that was created above. First, we set all its values to unit. The next line makes a **TransitionLayer**, setting the transition value between each pair of cells to the mean of the two cell values that are being connected. The **directions** argument is set to 8, which connects all cells to their 8 neighbours (Moore neighbourhood).

```
R> r[] <- 1
```

```
R> tr1 <- transition(r, transitionFunction=mean, directions=8)
```

If we inspect the object we created, we see that the resulting `TransitionLayer` object retains much information from the original `RasterLayer` object.

```
R> tr1
```

```
class      : TransitionLayer
dimensions : 3, 3, 9  (nrow, ncol, ncell)
resolution : 120, 60  (x, y)
extent     : -180, 180, -90, 90  (xmin, xmax, ymin, ymax)
coord. ref.: +proj=longlat +datum=WGS84
values     : conductance
matrix class: dsCMatrix
```

To illustrate how to create a asymmetric matrix, we first create a non-commutative distance function, `ncdf`. We then use this function as an argument in the function `transition`. To make sure that the resulting transition matrix is indeed asymmetric, we set the `symm` argument in `transition` to `FALSE`.

```
R> r[] <- runif(9)
R> ncf <- function(x) max(x) - x[1] + x[2]
R> tr2 <- transition(r, ncf, 4, symm=FALSE)
R> tr2
```

```
class      : TransitionLayer
dimensions : 3, 3, 9  (nrow, ncol, ncell)
resolution : 120, 60  (x, y)
extent     : -180, 180, -90, 90  (xmin, xmax, ymin, ymax)
coord. ref.: +proj=longlat +datum=WGS84
values     : conductance
matrix class: dgCMatrix
```

From the ‘matrix class’ we can deduce if the matrix is symmetric or not. These classes are defined in the package **Matrix** (Bates and Maechler 2012). The class `dsCMatrix` is for matrices that are symmetric. The class `dgCMatrix` holds an asymmetric matrix.

Different mathematical operations can be done with `Transition*` objects. This makes it possible to flexibly model different components of landscape friction.

```
R> tr3 <- tr1*tr2
R> tr3 <- tr1+tr2
R> tr3 <- tr1*3
R> tr3 <- sqrt(tr1)
```

Operations with more than one object require that the different objects have the same resolution and extent. Also, it is possible to extract and replace values in the matrix using indices, in a similar way to the use of indices with simple matrices.

```
R> tr3[cbind(1:9, 1:9)] <- tr2[cbind(1:9, 1:9)]
R> tr3[1:9, 1:9] <- tr2[1:9, 1:9]
R> tr3[1:5, 1:5]
```

5 x 5 sparse Matrix of class "dgCMatrix"

```
[1,] .          0.9750735 0.7132973 1.1730740 .
[2,] 0.4858214 .          0.5995594 .          1.229796
[3,] 0.4858214 0.8613355 .          .          .
[4,] 0.4858214 .          .          .          1.130796
[5,] .          0.7304475 .          0.8294477 .
```

The functions `adjacent` (from **raster**) and `adjacencyFromTransition` (from **gdistance**) can be used to create indices. Example 1 below gives an example.

Some functions require that **Transition*** objects do not contain any isolated ‘clumps’, islands that are not connected to the rest of the raster cells. This can be avoided when creating **Transition*** objects, for instance by giving conductance values between all adjacent cells a small minimum value. It can be checked visually if there are any clumps. There are several ways to visualize a **Transition*** object. For the first method, you can extract the transition matrix with function `transitionMatrix`. This gives a sparse matrix which can be visualized with function `image`. This shows the rows and columns of the transition matrix and indicates which has a non-zero value, which represents a connection between cells (Figure 3).

```
R> image(transitionMatrix(tr1))
```




Figure 3: Visualizing a **TransitionLayer** with function `image`.

Figure 3 shows which cells are connected to each other. A close observer of Figure 3 may wonder why cell 1 is connected to 5 different cells, as this cell is located in the upper left corner of the original grid. This is explained by the extent of this particular grid. Since it covers the whole world, the outer meridians (180 and -180 degrees) touch each other. The software takes this into account and as a result the cells in the extreme left column are connected to the extreme right column.

Figure 3 shows which cells contain non-zero values, but gives no further information about levels of conductance. The levels can be visualized by transforming the transition matrix back into a raster. To summarize the information in the transition matrix, we can take means or sums across rows or columns. Users can do this with function `raster`. For the different options see `method?raster("TransitionLayer")`. The default, shown in Figure 4, takes the column-wise means of the non-zero values.

```
R> plot(raster(tr3), main="raster(tr3)")
```




Figure 4: Visualizing a TransitionLayer using the function `raster`.

5. Correcting transition matrix values

The function `transition` calculates transition values based on the values of adjacent cells in the input raster. However, diagonal neighbours are more remote from each other than orthogonal neighbours. Secondly, on equirectangular (longitude-latitude) grids, West-East connections are longer at the equator and become shorter towards the poles, as the meridians approach each other. Therefore, the values in the matrix need to be corrected for these two types of distortion. Both types of distortion can be corrected by dividing each conductance matrix value by the distance between cell centres. This is what function `geoCorrection` does.

```
R> tr1C <- geoCorrection(tr1, type="c", multpl=FALSE)
```

```
R> tr2C <- geoCorrection(tr2, type="c", multpl=FALSE)
```

For least-cost type distances and routes, this works fine. However, as explained in Section 2 above, this does not work equally well for commute distances (random walks). The function `geoCorrection` corrects this distortion by multiplying the North-South transition values with the cosine of the average latitude of the cell centres. This type of correction is done by setting the argument `type` to `"r"`.

```
R> r3 <- raster(ncol=18, nrow=9)
R> r3 <- setValues(r3, runif(18*9)+5)
R> tr3 <- transition(r3, mean, 4)
R> tr3C <- geoCorrection(tr3, type="c", multpl=FALSE, scl=TRUE)
R> tr3R <- geoCorrection(tr3, type="r", multpl=FALSE, scl=TRUE)
```

As mentioned in Section 2, the effect of these distortions and corrections needs more research. The argument `scl` is set to `TRUE` to scale the transition values to a reasonable range. If the transition values are too large, commute distance and randomized shortest path functions will not work well. No scaling should be done if the user wants to obtain absolute distance values as output.

When `Transition*` objects with equal resolution and extent need to be corrected repetitively, computational effort may be reduced by preparing an object that only needs to be multiplied with the `Transition*` object to produce a corrected version of it. The following chunk of code is equivalent to the previous one.

```
R> CorrMatrix <- geoCorrection(tr3, type="r", multpl=TRUE, scl=TRUE)
R> tr3R <- tr3 * CorrMatrix
```

Object `CorrMatrix` is only calculated once. It can be multiplied with `Transition*` objects, as long as they have the same extent, resolution, and directions of cell connections. We need to take special care that the geo-correction multiplication matrix (`CorrMatrix`) contains all non-zero values that are present in the `Transition*` object with which it will be multiplied (`tr3` in this case).

6. Calculating distances

After obtaining the geographically corrected `Transition*` object, as we can calculate distances between points. It is important to note that all distance functions require a `Transition*` object with conductance values, even though distances will be expressed in 1/conductance (friction or resistance) units (see Section 3).

To calculate distances, we need to have the coordinates of point locations. This is done by creating a two-column matrix of coordinates. Functions will also accept a `SpatialPoints` object or, if there is only one point, a vector of length two.

```
R> sP <- cbind(c(-100, 100, -100), c(-50, 50, 50))
```

Calculating a distance matrix is straightforward now.

```
R> costDistance(tr3C, sP)
```

```
      1      2
2 1.4808140
3 0.8951392 0.9804259
```

```
R> commuteDistance(tr3R, sP)
```

```
      1      2
2 1071.3197
3 1011.7195 983.5072
```

```
R> rSPDistance(tr3R, sP, sP, theta=1e-12, totalNet="total")
```

```
      [,1]      [,2]      [,3]
[1,] 0.00000 60.95741 58.46170
[2,] 61.91810 0.00000 57.32414
[3,] 57.57795 55.47969 0.00000
```

The `costDistance` function relies on the package **igraph** (Csardi and Nepusz 2006) for the underlying calculation. It gives a symmetric or asymmetric distance matrix, depending on the `TransitionLayer` that is used as input.

Commute distance represents the random walk commute time, e.g., the number of cells traversed on the trip (Chandra *et al.* 1996).

`rSPDistance` gives the cost incurred during the same walk (θ approaches zero, so this is the cost incurred during a random walk, see Section 2). To obtain the commute costs we sum the corresponding off-diagonal elements: $d_{ij} + d_{ji}$. This is the distance of a commute from i to j and back from j to i .²

7. Dispersal paths

To determine dispersal paths of a (constrained) random walk, we use the function `passage`. This function can be used for both random walks and randomised shortest paths. The function calculates the number of passages through cells before arriving in the destination cell. Either the total or net number of passages can be calculated. The net number of passages is the number of passages that are not reciprocated by a passage in the opposite direction.

Figure 5 shows the probability of passage through each cell, assuming randomised shortest paths with the parameter θ set to 3.

```
R> origin <- SpatialPoints(cbind(0, 0))
R> rSPraster <- passage(tr3C, origin, sP[3,], theta=3)
```

²In this case, the commute costs (resistance) are close to the commute distances (number of steps). This is because the `TransitionLayer` object has been scaled, so that transition costs are close to unit for each step and the total number of steps and the total distance are of the same order of magnitude.




Figure 5: Probability of passage.

8. Path overlap and non-overlap

One of the specific uses for which package *gdistance* was created, is to look at trajectories coming from the same source ([van Etten and Hijmans 2010](#)). The degree of coincidence of two trajectories can be visualized by calculating the minimum of the probabilities of passage (Figure 6). With a more complex formula, we can approximate the non-overlapping part of the trajectory (Figure 7). This is done in the following code.

```
R> r1 <- passage(tr3C, origin, sP[1,], theta=1)
R> r2 <- passage(tr3C, origin, sP[3,], theta=1)
R> rJoint <- min(r1, r2)
R> rDiv <- max(max(r1, r2) * (1 - min(r1, r2)) - min(r1, r2), 0)
```




Figure 6: Overlapping part of the two routes.




Figure 7: Non-overlapping part of the two routes.

With the function `pathInc` we can calculate measures of path overlap and non-overlap for a large number of points. These measures can be used to predict patterns of diversity if these are due to dispersal from a single common source. If the argument `type` contains two or more elements, the result is a list of distances matrices. The default for `type` is to calculate joint and divergent length of the dispersal paths.

```
R> pathInc(tr3C, origin, sP)
```

```
$function1layer1
```

```
1      2
```

```
2 2.083425
3 2.355763 2.309920
```

```
$function2layer1
      1      2
2 2.784062
3 2.270096 2.406339
```

9. Example 1: hiking around Maunga Whau

The previous examples were somewhat theoretical, based on randomly generated values. More realistic examples serve to illustrate the various uses that can be given to this package.

Determining the fastest route between two points in complex terrain is useful for hikers. Tobler's Hiking Function provides a rough estimate of the maximum hiking speed (s) given the slope of the terrain (m) (Tobler 1993). The maximum speed of off-path hiking (in m/s) is:

$$s = 6e^{-3.5|m+0.05|}$$

Note that the function is not symmetric around 0 (see Figure 8).




Figure 8: Tobler's Hiking Function.

We use the Hiking Function to determine the shortest path to hike around the volcano Maunga Whau (Auckland, New Zealand). First, we read in the altitude data for the volcano. This is a geo-referenced version of a R base dataset (see `?volcano`).

```
R> r <- raster(system.file("external/maungawhau.grd",
+   package="gdistance"))
```

The Hiking Function requires the slope as input, which can be calculated from the altitude (z) and distance between cell centres (d).

$$m_{ij} = (z_j - z_i)/d_{ij}$$

The units of altitude and distance should be identical. Here, we use meters for both. First, we calculate the altitudinal differences between cells. Then we use the `geoCorrection` function to divide by the distance between cells.

```
R> altDiff <- function(x){x[2] - x[1]}
R> hd <- transition(r, altDiff, 8, symm=FALSE)
R> slope <- geoCorrection(hd, scl=FALSE)
```

Subsequently, we calculate the speed. We need to exercise special care, because the matrix values between non-adjacent cells is 0, but the slope between these cells is not 0! Therefore, we need to restrict the calculation to adjacent cells. We do this by creating an index for adjacent cells (`adj`) with the function `adjacent`. Using this index, we extract and replace adjacent cells, without touching the other values.

```
R> adj <- adjacent(r, cells=1:ncell(r), pairs=TRUE, directions=8)
R> speed <- slope
R> speed[adj] <- 6 * exp(-3.5 * abs(slope[adj] + 0.05))
```

Now we have calculated the speed of movement between adjacent cells. We are close to having the final conductance values. Attainable speed is a measure of the ease of crossing from one cell to another on the grid. However, we also need to take into account the distance between cell centres. Travelling with the same speed, a diagonal connection between cells takes longer to cross than a straight connection. Therefore, we use the function `geoCorrection` again!

```
R> x <- geoCorrection(speed, scl=FALSE)
```

This gives our final ‘conductance’ values. What do these values mean? The function `geoCorrection` divides the values in the matrix between the distance between cell centres. So, with our last command we calculated conductance (C) as follows:

$$C = s/d$$

This looks a lot like a measure that we are more familiar with, travel time (t):

$$t = d/s$$

In fact, the conductance values we have calculated are the reciprocal of travel time ($1/t$).

$$1/t = s/d = C$$

Maximizing the reciprocal of travel time is exactly equivalent to minimizing travel time. Distances calculated with this conductance matrix represent travel time according to the Hiking Function.

In the next step, we define two coordinates, A and B, and determine the paths between them. We test if the quickest path from A to B is the same as the quickest path from B back to A. The following code creates the shortest paths.

```
R> A <- c(2667670, 6479000)
R> B <- c(2667800, 6479400)
```

```
R> AtoB <- shortestPath(x, A, B, output="SpatialLines")
R> BtoA <- shortestPath(x, B, A, output="SpatialLines")
```

And this code was used to make Figure 9.

```
R> plot(r, main="")
R> lines(AtoB, col="red", lwd=2)
R> lines(BtoA, col="blue")
R> text(A[1] - 10, A[2] - 10, "A")
R> text(B[1] + 10, B[2] + 10, "B")
```

A small part of the A-B (red) and B-A (blue) lines in Figure 9 do not overlap. This is a consequence of the asymmetry of the Hiking Function.




Figure 9: Quickest hiking routes on Maunga Whau (A to B is red, B to A is blue).

10. Example 2: Geographical genetics

A correlation between genetic differentiation and geographic distance of individuals and populations is expected due to a mechanism known as isolation by distance ([Wright 1943](#)). This correlation is expected when random, symmetric dispersal occurs in homogeneous geographic spaces. For random dispersal in heterogeneous landscapes, recent work has shown that genetic differentiation correlates with the resistance distance between their locations ([McRae 2006](#)). Let's look at human genetic diversity in Europe, using the data presented by [Balaesque *et al.* \(2010\)](#).

First, we read in the data: a map of Europe, the coordinates of the populations (see [Figure 10](#)) and mutual genetic distances (see `?genDist` for more information on these data).

```
R> Europe <- raster(system.file("external/Europe.grd",
+   package="gdistance"))
R> Europe[is.na(Europe)] <- 0
R> data(genDist)
R> data(popCoord)
R> pC <- as.matrix(popCoord[c("x", "y")])
```

Then we create three geographical distance matrices. The first corresponds to the great-circle distance between populations. The second is the least-cost distance between locations. Travel is restricted to the land mass. The third is the commute distance (using the same conductance matrix), which is related to effective resistance between points if we conceive of the grid as an electrical circuit ([Chandra *et al.* 1996](#); [McRae 2006](#)).

```
R> geoDist <- pointDistance(pC, longlat=TRUE)
R> geoDist <- as.dist(geoDist)
R> Europe <- aggregate(Europe, 3)
R> tr <- transition(Europe, mean, directions=8)
R> trC <- geoCorrection(tr, "c", scl=TRUE)
R> trR <- geoCorrection(tr, "r", scl=TRUE)
R> cosDist <- costDistance(trC, pC)
R> resDist <- commuteDistance(trR, pC)
R> cor(genDist, geoDist)
```

```
[1] 0.5962655
```

```
R> cor(genDist, cosDist)
```

```
[1] 0.5889319
```

```
R> cor(genDist, resDist)
```

```
[1] 0.192114
```




Figure 10: Map of genotyped populations.

Among the distance measures evaluated until now, the great-circle distance between points turns out to be the best predictor of genetic distance. The other distance measures incorporate more information about the geographic space in which geneflow takes place, but do not improve the prediction. Presumably, the assumptions about geneflow incorporated in these distances are wrong. Prehistoric people in Europe did not move like wolves or drunkards...

Another assumption behind these distance measures is that dispersal is symmetric. This is often not the case. For example, diffusion from a single origin (Africa) explains much of the current geographical patterns of human genetic diversity ([Ramachandran *et al.* 2005](#)). As a result, the mutual genetic distance between a pair of humans from different parts from the globe depends on the extent they share their prehistoric migration history. Within Europe, genetic diversity is often thought to be a result of the migration of early Neolithic farmers from Anatolia (Turkey) to the west.

How well does a geographic wave of expansion from Anatolia explain the spatial pattern? The function `pathInc` calculates the overlap (and non-overlap) of dispersal paths from a common origin on the grid as a distance measure between points.

```
R> origin <- unlist(popCoord[22,c("x","y")])
```

```
R> pI <- pathInc(trC, origin=origin, from=pC,  
+   functions=list(overlap))  
R> cor(genDist,pI[[1]])
```

```
[1] -0.7178576
```

At least at first sight, the overlap of dispersal routes explains the spatial pattern better than any of the previous measures. The negative sign of the last correlation coefficient was expected, as more overlap in routes is associated with lower genetic distance. Additional work would be needed to improve predictions and compare the different models more rigorously.

11. Future work

Improvements of **gdistance** and methodological refinements are expected in various areas.

- All measures based on random walks depend critically on solving sparse linear systems. This is the most time-consuming part of the calculations. Faster libraries could improve the **gdistance** package if they become available in R in the future.
- Research on distances in graph theory is a very dynamic field in the computational sciences. New measures and algorithms could be added to **gdistance** when they become available.
- More research on the consequences of connecting grids in different ways is necessary, as indicated in Section 2. This should bring more precision to random walk calculations in geospatial analysis. Comparing the results of grid-based calculations to continuous space simulations or analytical solutions would be the way forward (Birch 2006).

12. Final remarks

Questions about the use of **gdistance** can be posted on the r-sig-geo email list. Bug reports and requests for additional functionality can be mailed to jacobvanetten@yahoo.com.

13. Acknowledgements

Work on the **gdistance** package started during the project “Collective Action for the Rehabilitation of Global Public Goods in the CGIAR Genetic Resources System: Phase 2” (2007-2010), under the guidance of Dr Robert Hijmans. Finalizing the package was undertaken as part of the CGIAR Research Program on Climate Change, Agriculture and Food Security (CCAFS), which is a strategic partnership of CGIAR and Future Earth. The views expressed in this document cannot be taken to reflect the official opinions of CGIAR or Future Earth.

References

- Balaresque P, Bowden G, Adams S, Leung HY, King T, Rosser Z, Goodwin J, Moison JP, Richard C, Millward A, Demain A, Barbujani G, Previdere C, Wilson I, Tyler-Smith C, Jobling M (2010). “A Predominantly Neolithic Origin for European Paternal Lineages.” *PLoS Biology*, **8**(1), e1000285.
- Bates D, Maechler M (2012). *Matrix: Sparse and Dense Matrix Classes and Methods*. R package version 1.0-5, URL <http://CRAN.R-project.org/package=Matrix>.
- Birch C (2006). “Diagonal and Orthogonal Neighbours in Grid-based Simulations: Buffon’s Stick after 200 Years.” *Ecological Modelling*, **192**(3-4), 637–644.
- Chandra A, Raghavan P, Ruzzo W, Smolensky R, Tiwari P (1996). “The Electrical Resistance of a Graph Captures its Commute and Cover Times.” *Computational Complexity*, **6**(4), 312–340.
- Csardi G, Nepusz T (2006). “The **igraph** Software Package for Complex Network Research.” *InterJournal*, p. 1695. URL <http://igraph.sf.net>.
- de Smith M, Goodchild M, Longley P (2009). *Geospatial Analysis*. Matador.
- Dijkstra E (1959). “A Note on Two Problems in Connexion with Graphs.” *Numerische Mathematik*, **1**(1), 269–271.
- Doyle P, Snell J (1984). *Random Walks and Electric Networks*. Carus Mathematical Monographs 22. Mathematical Association of America.
- Fouss F, Pirotte A, Renders JM, Saelens M (2007). “Random-Walk Computation of Similarities between Nodes of a Graph with Application to Collaborative Recommendation.” *IEEE Transactions on Knowledge and Data Engineering*, **19**(3), 355–369. ISSN 1041-4347. doi:10.1109/TKDE.2007.46.
- GRASS Development Team (2012). *Geographic Resources Analysis Support System (GRASS GIS) Software*. Open Source Geospatial Foundation, USA. URL <http://grass.osgeo.org>.
- Hijmans RJ, van Etten J (2012). *raster: Geographic Data Analysis and Modeling*. R package version 2.0-31, URL <http://CRAN.R-project.org/package=raster>.
- Kivimäki I, Shimbo M, Saelens M (2012). “Developments in the Theory of Randomized Shortest Paths with a Comparison of Graph Node Distances.” *ArXiv e-prints*. URL <http://adsabs.harvard.edu/abs/2012arXiv1212.1666K>.
- McCoy J, Johnston K (2002). *Using ArcGIS Spatial Analyst*. ESRI.
- McRae B (2006). “Isolation by Resistance.” *Evolution*, **60**(8), 1551–1561.
- McRae B, Dickson B, Keitt T, Shah V (2008). “Using Circuit Theory to Model Connectivity in Ecology, Evolution, and Conservation.” *Ecological Modelling*, **89**(10), 2712–2724. doi:10.1890/07-1861.1.
- R Development Core Team (2014). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. ISBN 3-900051-07-0, URL <http://www.R-project.org/>.

- Ramachandran Sand Deshpande O, Roseman C, Rosenberg N, Feldman M, Cavalli-Sforza L (2005). "Support from the Relationship of Genetic and Geographic Distance in Human Populations for a Serial Founder Effect Originating in Africa." *Proceedings of the National Academy of Science*, **102**(44), 15942–15947.
- Saerens M, Yen L, Fouss F, Achbany Y (2009). "Randomized Shortest-Path Problems: Two Related Models." *Neural Computation*, **21**(8), 2363–2404.
- Tobler W (1970). "A Computer Movie Simulating Urban Growth in the Detroit Region." *Economic Geography*, **46**(2), 234–240.
- Tobler W (1993). "Three Presentations on Geographical Analysis and Modeling." URL http://www.ncgia.ucsb.edu/Publications/Tech_Reports/93/93-1.PDF.
- van Etten J, Hijmans R (2010). "A Geospatial Modelling Approach Integrating Archaeobotany and Genetics to Trace the Origin and Dispersal of Domesticated Plants." *PLoS ONE*, **5**(8), e12060.
- Wright S (1943). "Isolation by Distance." *Genetics*, **28**(2), 114–138.

Affiliation:

Jacob van Etten
Biodiversity International
c/o CATIE, Turrialba, Costa Rica
E-mail: jacobvanetten@yahoo.com
URL: <http://biodiversityinternational.org>