

# Package ‘SlideDesignerGUI’

July 27, 2015

**Version** 1.6.2

**Date** 2015-07-14

**Title** Slide Designer GUI Package

**Author** P. Roebuck, based on earlier work by Kevin R. Coombes

**Maintainer** ``P. Roebuck'' <proebuck@mdanderson.org>

**Description** Graphical User Interface for recording layout of a slide design.

**Depends** R (>= 2.15)

**Imports** tcltk, tclish (>= 1.0.0)

**SystemRequirements** Tcl/Tk

**NeedsCompilation** no

**URL** <http://supercurve.r-forge.r-project.org/#SlideDesignerGUI>

**License** Artistic-2.0

**Copyright** file COPYRIGHTS

**LazyLoad** yes

**Repository** R-Forge

**Repository/R-Forge/Project** supercurve

**Repository/R-Forge/Revision** 978

**Repository/R-Forge/DateTimeStamp** 2015-07-27 04:00:08

**Date/Publication** 2015-07-27 04:00:08

## R topics documented:

SlideDesignerGUI-package . . . . .	2
slidedesignerGUI . . . . .	2

## Index

4

---

**SlideDesignerGUI-package**

*Package for slide design layout*

---

**Description**

A package for recording layout of a slide design.

**Details**

Package: SlideDesignerGUI  
Type: Package  
Version: 1.6.2  
Date: 2015-07-14  
License: Artistic-2.0

For a complete list of functions, use `library(help="SlideDesignerGUI")`.

For a high-level summary of the changes for each revision, use  
`file.show(system.file("NEWS", package="SlideDesignerGUI"))`.

**Author(s)**

P. Roebuck <proebuck@mdanderson.org>

---

**slidedesignerGUI**

*Graphical User Interface for slide design layout*

---

**Description**

Graphical User Interface for recording layout of a slide design.

**Usage**

`slidedesignerGUI()`  
`sdui()`

**Details**

The function `slidedesignerGUI` launches a Graphical User Interface for recording the layout of positive and negative controls of a slide design, used with the **SuperCurve** package. The GUI uses Tk widgets (via the R-Tcl/Tk interface by Peter Dalgaard) in order to provide a simple interface.

The function `sdui` is an alias for the aforementioned function.

## Resources

The Tk options database is loaded from user-specific defaults files, such as ‘.Xdefaults’, and resource databases loaded into the X server. The package will attempt to load its resources upon startup, following the X11R5 method of merging app-default files from multiple sources. The standard X11 paths are searched first, followed by paths specified by the environment variables XFILESEARCHPATH, XAPPLRESDIR, XUSERFILESEARCHPATH, respectively. Unlike X11, **ALL** matching files will be loaded, not just the first.

One way to make use of the options database is to create a file named ‘slidedesignerGUI.ad’ in your home directory, specifying any desired resources. Set your XUSERFILESEARCHPATH environment variable within R with the command:

```
Sys.setenv(XUSERFILESEARCHPATH=file.path(path.expand("~/"), "%N.ad"))
```

## Author(s)

P. Roebuck <proebuck@mdanderson.org>

## Examples

```
## Not run:  
slidedesignerGUI()  
# -or-  
sdui()  
  
## End(Not run)
```

# Index

\*Topic **IO**

    slidedesignerGUI, [2](#)

\*Topic **package**

    SlideDesignerGUI-package, [2](#)

sdui (slidedesignerGUI), [2](#)

    slidedesignerGUI, [2](#)

    SlideDesignerGUI-package, [2](#)